



Eulerian Cradle 512.1

General Information:

The Eulerian cradles of the series 500 can be combined with the goniometers of the series 400 to create multi-circle diffractometers. These can be used for analytical investigations in the fields of X-ray and neutron diffraction.

The Eulerian cradle is a full-circle cradle with an assymetrical design. The Phi- and Chi-circle planes are at right angles to one another.

The motor and signal currents are transmitted via slip rings. This enables an unrestricted rotation around both axes.

A manual Z-adjustment 5104.A05 is incorporated in the Phi-circle, enabling goniometer heads of the series 1000 to be mounted. Also available is a motorised Z-adjustment.

For sample adjustment an optical microscope or an optional CCDcamera is integrated (see Accessories MiniVID).

Both circles are equipped with zero-point controls and step motors. A range of different motor types and specifications is available according to customer requirements.

It is possible to equip the Eulerian cradle with a cryostat mount and/or counter bearings for mounting individually required equipment.

Specifications:

Sphere of confusion [mm]:	0.02***
Parallelity (Chi-plane to Phi-axis) ["]:	<= +/- 10***
Weight [kg]:	64

	Phi-Circle	Chi-Circle
Travel range [°]:	360	360
Gear ratio:	360:1 / 180:1**	360:1
Accuracy ["]:	30	30
Repeatability (unidir.) ["]:	<= 2	<= 3
Reversal error ["]:	<= 10	<= 15
Resolution [°]:	0.001* / 0.002* **	0.001*
Min. drive torque [Nm]:	0.10 / 0.13**	1.5
Flange size [mm]:	56	83


^{*} step motor, 1000 steps/revolution



** using Goniometer 410A

*** with a load of 10kg

Dimensions [mm]:



Accessories:

included Motors: Limit switches: included Zero-point control: included 2056.05 (Phi) Gear boxes: 2056.10 (Phi) 2056.20 (Phi) 2083.05 (Chi) 2083.10 (Chi) 2083.20 (Chi) Encoder: incremental absolute Steuerung: 9300 CCD-camera: MiniVID Cryostat mount: 512.12 512.12M Counter bearing: 512.11 Motor. Z-adjustment: 5104.A05M Goniometer heads: Series 1000



